

10/11/05
(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 280 039 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
29.01.2003 Bulletin 2003/05

(51) Int Cl.7: G06F 1/00

(21) Application number: 02252949.9

(22) Date of filing: 25.04.2002

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR

Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 26.07.2001 US 912391

(71) Applicant: Networks Associates Technology Inc.
Santa Clara, CA 95054 (US)

(72) Inventors:

- Hursey, Neil John
Hertford Heath, Hertfordshire SG13 7RB (GB)
- McEwan, William Alexander
Newton Blossomville, Beds. MK43 8AJ (GB)

(74) Representative:

Robinson, Nigel Alexander Julian
D. Young & Co.,
21 New Fetter Lane
London EC4A 1DA (GB)

(54) Detecting e-mail propagated malware

(57) An e-mail client serves to detect mass mailing malware by detecting if over a threshold number of addressees from within the address book of that e-mail client are being sent an e-mail or over a predetermined number of substantially identical e-mails are being sent by that e-mail client. The sending of e-mail messages to a substantial proportion of the addressees within an

address book is a characteristic indicative of mass mailing malware. A quarantine queue may be provided in which e-mail messages are held for a predetermined period prior to being sent out in order that separate e-mail messages being sent to a large proportion of the address book addressees may be identified and linked together.




FIG. 3

EP 1 280 039 A2

Description

[0001] This invention relates to data processing systems. More particularly, this invention relates to the detection of e-mail propagated malware.

[0002] Some of the most prolific and damaging computer viruses in recent times have replicated and distributed themselves by use of the victim's e-mail service. The virus is received in an e-mail and when activated serves to replicate and send itself to most, if not all, of the e-mail addresses listed in the victim's e-mail address book. The infected e-mail is then received by another unsuspecting user who again causes it to replicate it propagate.

[0003] Network Associates, Inc. provide a server based computer program called Outbreak Manager that operates upon an e-mail server to detect patterns of mail traffic behaviour indicative of such a virus outbreak and progressively to apply counter-measures against that outbreak. This activity necessarily places a data processing load upon the e-mail server and tends to detect a virus outbreak only when this has escalated to at least some extent of mass behaviour.

[0004] A further mechanism for suppressing mass mail viruses is described in commonly assigned co-pending United States Application No.: USSN 09/678,688, the disclosure of which mechanism is incorporated herein by reference.

[0005] Viewed from one aspect the present invention provides a computer program product operable to control an e-mail client computer to detect e-mail propagated malware, said computer program product comprising:

e-mail generating logic operable to generate an e-mail message;
comparison logic operable to compare said e-mail message with at least one of an address book of a sender of said e-mail message and one or more previously generated e-mail messages from said client computer; and
identifying logic operable to identify said e-mail message as potentially containing malware if at least one of:

- (i) said e-mail message is being sent to more than a threshold number of addressees specified within said address book;
- (ii) said e-mail message contains message content having at least a threshold level of similarity to message content of said previously generated e-mail messages being sent to more than a threshold number of addressees specified within said address book; and
- (iii) said e-mail message contains message content having at least a threshold level of similarity to message content of more than a threshold number of said previously generated

e-mail messages.

[0006] The invention recognises that an e-mail client computer can act to detect many mass mailing malware problems since this type of malware will often produce characteristic and abnormal behaviour on the e-mail client computer itself which behaviour may be detected and used to trigger action to stop the outbreak at an early stage. Furthermore, placing a processing load upon the client computers rather than the e-mail server distributes the processing load more widely in an advantageous fashion. The characteristic behaviour on the e-mail client computer itself can take a variety of forms, but is at least one of generating an e-mail message sent to greater than a given number of addressees within the address book associated with that client computer (either as a single e-mail or as a series of e-mails sharing substantially the same message content) or as a series of e-mail messages containing substantially the same message content exceeding a predetermined threshold number.

[0007] It will be appreciated that the threshold number of addressees within the address book could be defined in a variety of different ways. As an example, it could be defined as an absolute number, but in preferred embodiments is defined as a predetermined (user specified) proportion of the total number of addressees within the address book.

[0008] The message content of e-mail messages could be compared in a variety of different ways. E-mail messages could be identified as similar only when they were identical. However, in order to provide protection against malware which seeks to disguise itself, preferred embodiments of the invention identify message content as the same when a predetermined level of similarity is detected, such as for example by using known algorithms like those found within the WinDiff program.

[0009] In order to help resist mass mailed malware which propagates itself as a sequence of separate e-mail messages directed to individual addressees (or a relatively small number of addressees), preferred embodiments of the invention utilise a quarantine queue from which outbound messages are held for a predetermined period before being sent on. This allows messages to be compared with one another to identify those having above a predetermined level of similarity in order that they may be identified as potentially carrying malware and appropriate counter-measures triggered.

[0010] The non-realtime nature of e-mail delivery and the relatively high processing speeds of e-mail systems are such that the quarantine period may be kept relatively low, say several seconds, without producing a noticeable impact on the system performance for a user and yet sufficient time for a sequence of related e-mails to be generated by a malware program and accordingly detected before the first of those e-mails is sent from the client computer out to the addressee.

[0011] It will be appreciated that the characteristics of

mass mailed malware discussed above are not necessarily definitive as there may be good reasons why a genuine e-mail message, or sequence of e-mail messages, may be generated by a user and yet have these properties. Accordingly, preferred embodiments of the invention act to trigger user confirmation of the nature of an e-mail message identified as potentially containing malware before it is issued.

[0012] Patterns of behaviour within an administered group of computers or patterns of behaviour of an individual user may be more readily recognised in preferred embodiments in which when an item of potential malware is identified a message is sent to an administrator of the system.

[0013] Preferred embodiments of the invention may speed processing by seeking to identify potential malware only within e-mail messages that have an executable element (e.g. an executable attachment or HTML body) as an executable payload is required by a virus propagating e-mail.

[0014] Further aspects of the invention provide a method for detecting malware within a client computer and an apparatus for detecting malware within a client computer.

[0015] Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Figures 1 and 2 illustrate two examples of how an anti-virus mechanism may be combined with an e-mail client and an operating system within a client computer;

Figure 3 is a flow diagram schematically illustrating processing performed upon generation of an e-mail message by a client computer;

Figure 4 is a flow diagram schematically illustrating receipt of an e-mail message into a quarantine queue within a client computer program;

Figure 5 is a flow diagram illustrating removal of an e-mail message from the quarantine queue after its quarantine period expires; and

Figure 6 is a schematic diagram of a general purpose computer of the type which may be used to perform the above described techniques.

[0016] Figure 1 schematically illustrates software elements within a client computer. An operating system 2 is provided for controlling interaction of the computer hardware with higher level computer software. In the case of the Windows operating system produced by Microsoft Corporation, the operating system 2 provides a Messaging Application Programming Interface that is used by application programs wishing to use messaging functionality, such as e-mails, in order to interact with the underlying messaging systems. An e-mail client computer program 4 is used by a user to generate and receive e-mail messages. An example of such an e-mail client computer program would be Microsoft Outlook

produced by Microsoft Corporation.

[0017] Disposed between the e-mail client computer program 4 and the operating system 2 is the anti-virus mechanism 6. In Figure 1 example this anti-virus mechanism 6 serves to receive all MAPI requests from the e-mail client computer program 4 and generate any MAPI responses to the e-mail client computer program 4. The anti-virus mechanism 6 has a further interface with the operating system 2 to which the intercepted messages are sent or from which intercepted messages are received. Having intercepted this traffic, the anti-virus mechanism 6 can apply the techniques described hereinafter to resist mass mailing malware.

Figure 2 illustrates an alternative arrangement in which the e-mail client computer program 4' is modified to send all its outbound messages to an anti-virus mechanism 8 for checking for mass mailing malware behaviour prior to a pass/fail result being returned from the anti-virus mechanism 8 indicating that the e-mail client 4' can issue the e-mail message and to the operating system 2.

[0018] Both the arrangement of Figure 1 and Figure 2 will be familiar to programmers in the application program field as ways of adding new functionality in combination with existing programs and mechanisms by redirecting and intercepting messages passed between those programs and mechanisms.

[0019] Figure 3 schematically illustrates processing performed upon generation of a new e-mail message within an e-mail client computer program. At step 10 the system waits for a new e-mail message to be generated. When a new e-mail message is generated, processing proceeds to step 12 at which the addressees of the e-mail message are identified and compared with the contents of the address book for the client computer user who is sending the e-mail message and a determination made as to the percentage of the total address book addressees who are being addressed by the new e-mail message. At step 14 this determined percentage is compared with a threshold level (which may be a user specified parameter or within a more managed environment an administrator specified value). If the threshold value is exceeded, then this is indicative of behaviour characteristic of a malware containing e-mail message. Accordingly, step 16 serves to generate an appropriate warning message to the user of the client e-mail computer program seeking confirmation from the user that the e-mail message should in fact be sent. In this way, if the message was not one genuinely produced by the user, such as one automatically generated by an item of malware inappropriately reading the user's address book to propagate itself, then the user will not confirm the message for sending at step 18 and processing will be directed to step 20. Step 20 serves to generate a warning message that is sent to a system administrator before processing proceeds to step 22 at which the e-mail message is deleted. If this were a stand-alone system, then step 20 could be deleted. In some systems

step 20 could instead send a message to an anti-virus computer program provider to provide warning of new malware outbreaks, possibly including forwarding a copy of the e-mail message which had been identified as containing the malware.

[0020] If at step 18 the user confirmed the message was to be sent then processing proceeds to step 24 at which the e-mail is sent out from the client computer.

[0021] If the test at step 14 did not indicate that the threshold was exceeded, then processing proceeds to step 26. Step 26 determines whether or not e-mail message contains executable material, such as any executable attachments or an HTML body which could be executable. If the e-mail message does not have any executable content, then it may not serve as a vector for a virus and accordingly processing proceeds to step 24 at which the e-mail message is sent. However, if the test at step 26 indicates executable content, then processing proceeds to step 28 at which the e-mail message is added to a quarantine queue as will be described below.

[0022] After any one of steps 22, 24 and 28 processing of the e-mail message generated terminates for this processing flow and the system returns to step 10 to await generation of the next e-mail message.

[0023] Figure 4 illustrates the action of the quarantine queue. At step 30 the system waits to receive an e-mail message as issued from step 28 of Figure 3. When an e-mail message is received, step 32 serves to compare the received e-mail message with any existing messages currently held within the quarantine queue. The comparison could be one which identifies identical messages, or one which is more sophisticated and identifies as the same any messages sharing above a predetermined threshold level of content. An alternative would be to identify as the same any messages sharing a common attachment, as such attachments are typically the primary element of the malware. Step 34 determines if the received message is a new message. If the message is a new message, then step 36 adds it to the list of unique messages currently held within the quarantine queue and against which further received messages are to be compared. If the received message is not a new message, then processing proceeds to step 38 at which score values indicative of the messages held within the quarantine queue representing malware are updated. These score values may be one or more of a score indicating what proportion of the total content of the sender's address book have been sent a message sharing substantially the same content, either as a percentage of the address book or possibly in terms of an absolute number. Alternatively a simple count of the number of queued messages sharing substantially the same message content may be used.

[0024] At step 40 the updated score values are compared with threshold values, which again may be user or administrator specified. At step 42 any message which is now exceeding one of the threshold values is identified. If no message is identified, then processing

of this received e-mail message terminates and the system returns to step 30 to await the next e-mail message. If an e-mail message does cause a threshold to be exceeded at step 42, then processing proceeds to step 44 at which a user and/or administrator warning message is generated giving details of the message exceeding the threshold value. At step 46 the user's confirmation that the message should be sent is sought. Depending upon the user's input, the message is either sent at step 48 or deleted at step 50 before processing again returns to step 30.

[0025] Figure 5 is a flow diagram illustrating the removal of messages from the quarantine queue. The processing of Figure 5 may take place as a separate thread/process compared to those previously discussed. At step 52 a determination is made as to whether or not any of the messages currently held within the quarantine queue have been held there for longer than a predetermined (user or administrator specified) quarantine period. If any such messages are identified, then processing proceeds to step 54 at which they are sent out from the quarantine queue to their destination. Alternatively, processing terminates for a delay period until the next check of the quarantine queue for messages to be released is scheduled.

[0026] Figure 6 schematically illustrates a general purpose computer 200 of the type that may be used to implement the above techniques. The general purpose computer 200 includes a central processing unit 202, a random access memory 204, a read only memory 206, a hard disk drive 208, a display driver 210 and display 212, a user input/output circuit 214 and keyboard 216 and mouse 218 and a network interface unit 220 all connected via a common bus 222. In operation the central processing unit 202 executes program instructions stored within the random access memory 204, the read only memory 206 or the hard disk drive 208. The working memory is provided by the random access memory 204. The program instructions could take a variety of forms depending on the precise nature of the computer 200 and the programming language being used. The results of the processing are displayed to a user upon the display 212 driven by the display driver 210. User inputs for controlling the general purpose computer 200 are received from the keyboard 216 and the mouse 218 via the user input/output circuit 214. Communication with other computers, such as exchanging e-mails, downloading files or providing internet or other network access, is achieved via the network interface unit 220.

[0027] It will be appreciated that the general purpose computer 200 operating under control of a suitable computer program may perform the above described techniques and provide apparatus for performing the various tasks described. The general purpose computer 200 also executes the method described previously. The computer program product could take the form of a recordable medium bearing the computer program, such as a floppy disk, a compact disk or other recordable medium.

Alternatively, the computer program could be dynamically downloaded via the network interface unit 220.

[0028] It will be appreciated that the general purpose computer 200 is only one example of the type of computer architecture that may be employed to carry out the above described techniques. Alternative architectures are envisaged and are capable of use with the above described techniques.

Claims

1. A computer program product operable to control an e-mail client computer to detect e-mail propagated malware, said computer program product comprising:

e-mail generating logic operable to generate an e-mail message;
comparison logic operable to compare said e-mail message with at least one of an address book of a sender of said e-mail message and one or more previously generated e-mail messages from said client computer; and
identifying logic operable to identify said e-mail message as potentially containing malware if at least one of:

- (i) said e-mail message is being sent to more than a threshold number of addressees specified within said address book;
- (ii) said e-mail message contains message content having at least a threshold level of similarity to message content of said previously generated e-mail messages being sent to more than a threshold number of addressees specified within said address book; and
- (iii) said e-mail message contains message content having at least a threshold level of similarity to message content of more than a threshold number of said previously generated e-mail messages.

2. A computer program product as claimed in claim 1, wherein said e-mail message specifies a plurality of addressees, said comparison logic being operable to compare said plurality of addressees with said e-mail address book to determine if said at least a threshold number of addressees has been exceeded.

3. A computer program product as claimed in claims 1 and 2, wherein said at least a threshold number of addressees is specified as a proportion of addressees within said address book.

4. A computer program product as claimed in claim 3,

wherein said proportion of addressees within said address book is user specified.

5. A computer program product as claimed in any one of the preceding claims, comprising quarantine queue logic operable to hold said previously generated e-mail messages in a quarantine queue for at least a predetermined quarantine period prior to being sent from said client computer.

6. A computer program product as claimed in claim 5, wherein said quarantine period is user specified.

7. A computer program product as claimed in any one of the preceding claims, comprising confirmation input logic operable when said e-mail message is identified as potentially containing malware to generate a user message seeking a confirmation input from a user of said client computer before said e-mail message is sent.

8. A computer program product as claimed in any one of the preceding claims, comprising administrator warning logic operable when said e-mail message is identified as potentially containing malware to send an administrator warning message to an administrator of said client computer regarding said e-mail message.

9. A method of detecting e-mail propagated malware within an e-mail client computer, said method comprising the steps of:

generating an e-mail message;
comparing said e-mail message with at least one of an address book of a sender of said e-mail message and one or more previously generated e-mail messages from said client computer; and
identifying said e-mail message as potentially containing malware if at least one of:

- (i) said e-mail message is being sent to more than a threshold number of addressees specified within said address book;
- (ii) said e-mail message contains message content having at least a threshold level of similarity to message content of said previously generated e-mail messages being sent to more than a threshold number of addressees specified within said address book; and
- (iii) said e-mail message contains message content having at least a threshold level of similarity to message content of more than a threshold number of said previously generated e-mail messages.

10. A method as claimed in claim 9, wherein said e-mail message specifies a plurality of addressees, said plurality of addressees being compared with said e-mail address book to determine if said at least a threshold number of addressees has been exceeded. 5
11. A method as claimed in any one of claims 9 and 10, wherein said at least a threshold number of addressees is specified as a proportion of addressees within said address book. 10
12. A method as claimed in claim 11, wherein said proportion of addressees within said address book is user specified. 15
13. A method as claimed in any one of claims 9, 10 and 11, wherein said previously generated e-mail messages are held in a quarantine queue for at least a predetermined quarantine period prior to being sent from said client computer. 20
14. A method as claimed in claim 13, wherein said quarantine period is user specified. 25
15. A method as claimed in any one of claims 9 to 14, wherein when said e-mail message is identified as potentially containing malware, then a user message is generated seeking a confirmation input from a user of said client computer before said e-mail message is sent. 30
16. A method as claimed in any one of claims 9 to 15, wherein when said e-mail message is identified as potentially containing malware, then an administrator warning message is sent to an administrator of said client computer regarding said e-mail message. 35
17. Apparatus for detecting e-mail propagated malware within a client computer, said apparatus comprising: 40
 - an e-mail generator operable to generate an e-mail message;
 - a comparator operable to compare said e-mail message with at least one of an address book of a sender of said e-mail message and one or more previously generated e-mail messages from said client computer; and
 - a malware identifier operable to identify said e-mail message as potentially containing malware if at least one of: 50
 - (i) said e-mail message is being sent to more than a threshold number of addressees specified within said address book; 55
 - (ii) said e-mail message contains message content having at least a threshold level of similarity to message content of said previously generated e-mail messages being sent to more than a threshold number of addressees specified within said address book; and
 - (iii) said e-mail message contains message content having at least a threshold level of similarity to message content of more than a threshold number of said previously generated e-mail messages.
18. Apparatus as claimed in claim 17, wherein said e-mail message specifies a plurality of addressees, said comparator being operable to compare said plurality of addressees with said e-mail address book to determine if said at least a threshold number of addressees has been exceeded.
19. Apparatus as claimed in any one of claims 17 and 18, wherein said at least a threshold number of addressees is specified as a proportion of addressees within said address book.
20. Apparatus as claimed claim 19, wherein said proportion of addressees within said address book is user specified.
21. Apparatus as claimed in any one of claims 17, 18, 19 and 20, comprising a quarantine queue operable to hold said previously generated e-mail messages in a quarantine queue for at least a predetermined quarantine period prior to being sent from said client computer.
22. Apparatus as claimed in claim 21, wherein said quarantine period is user specified.
23. Apparatus as claimed in any one of claims 17 to 22, comprising a confirmation input unit operable when said e-mail message is identified as potentially containing malware to generate a user message seeking a confirmation input from a user of said client computer before said e-mail message is sent.
24. Apparatus as claimed in any one of claims 17 to 23, comprising an administrator warning unit operable when said e-mail message is identified as potentially containing malware to send an administrator warning message to an administrator of said client computer regarding said e-mail message.




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 1 280 039 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
17.08.2005 Bulletin 2005/33

(51) Int Cl.7: **G06F 1/00**

(43) Date of publication A2:
29.01.2003 Bulletin 2003/05

(21) Application number: **02252949.9**

(22) Date of filing: **25.04.2002**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE TR**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventors:
• **Hursey, Neil John**
Hertford Heath, Hertfordshire SG13 7RB (GB)
• **McEwan, William Alexander**
Newton Blossomville, Beds. MK43 8AJ (GB)


(30) Priority: **26.07.2001 US 912391**

(74) Representative:
Robinson, Nigel Alexander Julian
D Young & Co
120 Holborn
London EC1N 2DY (GB)

(71) Applicant: **Networks Associates Technology, Inc.**
Santa Clara, CA 95054 (US)

(54) Detecting e-mail propagated malware

(57) An e-mail client serves to detect mass mailing malware by detecting if over a threshold number of addressees from within the address book of that e-mail client are being sent an e-mail or over a predetermined number of substantially identical e-mails are being sent by that e-mail client. The sending of e-mail messages to a substantial proportion of the addressees within an address book is a characteristic indicative of mass mailing malware. A quarantine queue may be provided in which e-mail messages are held for a predetermined period prior to being sent out in order that separate e-mail messages being sent to a large proportion of the address book addressees may be identified and linked together.

**FIG. 3****EP 1 280 039 A3**



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 25 2949

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	WO 01/46872 A (PACE, MARK, RAYMOND; TALLEY, BROOKS, CASH) 28 June 2001 (2001-06-28) * abstract * * page 3, last line - page 5, line 4 * * page 7, line 10 - line 18 * * page 7, line 28 - line 34 * -----	1,5-9, 13-17, 21-24	G06F1/00
X,P	WO 02/19069 A (CONTENT TECHNOLOGIES LIMITED; HOCKEY, ALYN; CLEARSWIFT LIMITED) 7 March 2002 (2002-03-07) * page 6, line 1 - line 25 * * page 8, line 5 - line 35 * * page 19, line 21 - line 24 * * page 22, line 1 - line 28 * * page 24, line 11 - line 15 * -----	1,9,17	
Y	HOWLETT D: "SCREENING YOUR E-MAIL CONTENTS" PC USER, LONDON, GB, no. 266, 6 September 1995 (1995-09-06), page 58, XP000617461 * the whole document * -----	1-24	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Y	LONN R: "Re: automated spam detection" 16 February 1999 (1999-02-16), , XP002229453 * the whole document * -----	1-24	G06F H04L
Y	WO 99/14909 A (BRITISH TELECOMMUNICATIONS PUBLIC LIMITED COMPANY; CHALMERS, JONATHAN,) 25 March 1999 (1999-03-25) * page 4, line 5 - line 7 * * page 6, line 14 - line 18 * * page 7, line 24 - line 26 * * page 16, line 3 - line 14 * * claim 4 * ----- -/--	1-24	
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 24 June 2005	Examiner Arbutina, E
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 25 2949

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	<p>GARBER L: "MELISSA VIRUS CREATES A NEW TYPE OF THREAT"</p> <p>COMPUTER, IEEE COMPUTER SOCIETY, LONG BEACH., CA, US, US, vol. 32, no. 6, June 1999 (1999-06), pages 16-19, XP000829612</p> <p>ISSN: 0018-9162</p> <p>* page 16, right-hand column, line 37 - line 46 *</p> <p>* page 17, right-hand column, last line - page 18, left-hand column, line 10 *</p> <p>-----</p>		
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
The Hague		24 June 2005	Arbutina, L
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone</p> <p>Y : particularly relevant if combined with another document of the same category</p> <p>A : technological background</p> <p>O : non-written disclosure</p> <p>P : intermediate document</p> <p>T : theory or principle underlying the invention</p> <p>E : earlier patent document, but published on, or after the filing date</p> <p>D : document cited in the application</p> <p>L : document cited for other reasons</p> <p>.....</p> <p>& : member of the same patent family, corresponding document</p>			

1
EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 25 2949

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

24-06-2005

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0146872	A	28-06-2001	US 6460050 B1	01-10-2002
			AU 4525901 A	03-07-2001
			EP 1242921 A1	25-09-2002
			JP 2004500761 T	08-01-2004
			WO 0146872 A1	28-06-2001

WO 0219069	A	07-03-2002	GB 2366706 A	13-03-2002
			AU 8235901 A	13-03-2002
			EP 1368719 A2	10-12-2003
			WO 0219069 A2	07-03-2002
			US 2004064515 A1	01-04-2004

WO 9914909	A	25-03-1999	AU 8880198 A	05-04-1999
			WO 9914909 A1	25-03-1999

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82